



Flush Stucco
Model 5210 (2" thick R-17.66)
Model 5710 (134" thick R-16.18)
TL Windows p24
Bevelite p24 (5710 only)
Carriage Windows p25
Ranch Windows p26
Standard Windows p27



V-Groove Stucco Model 5212 (2" thick R-17.66) Model 5712 (1¾" thick R-16.18) TL Windows p24 (bottom)



Raised Ranch Stucco Panel Model 5270 (2" thick R-17.66) Model 5770 (1¾" thick R-16.18) Bevelite p24 (5770 only) Ranch Windows p26



Raised Standard Stucco Panel Model 5280 (2" thick R-17.66) Model 5780 (13" thick R-16.18) Bevelite p24 (5780 only) Standard Windows p27







available rigid/flexible vinyl door stop.



INSULATEI Aluminun

A Superior Alternative

Mother Nature throws some pretty nasty weather at your home. That's why Haas Door created the 5000 Series: the strength of an insulated garage door combined with long-lasting and corrosion-resistant aluminum. Filled with dense CFC- free polyurethane foam insulation, 5200 models are 2 inches thick with a calculated R-value of 17.66, while 5700 models are 1% inches thick and have a calculated R-value of 16.18.

5000 Series doors feature a tough, durable and weather-resistant Trinar® paint finish. Exposed for decades at weathering facilities in South Florida and other locations around the world, testing has proven Trinar® paints are more than capable of withstanding the degrading effects of weather extremes from the equator to the arctic. Backed by a limited lifetime warranty, the 5000 series is built to last while providing distinction and style.





A Full Thermal Break is used in the tongue-and-

groove construction of all 5000 series doors. This rigid vinyl extrusion seals